

bird 2 auf Debian Buster installieren

Abhängigkeiten installieren

```
apt install build-essential autotools-dev autoconf flex bison libncurses-dev  
libreadline-dev
```

bird2 bauen und installieren

```
wget https://bird.network.cz/download/bird-2.0.7.tar.gz  
tar -xf bird-2.0.7.tar.gz  
ls -al  
cd bird-2.0.7/  
./configure  
make -j 2  
sudo make install
```

bird2 einrichten

```
adduser --system --group --no-create-home bird
```

[/etc/systemd/system/bird.service](#)

```
[Unit]  
Description=BIRD Internet Routing Daemon  
After=network.target  
  
[Service]  
ExecStartPre=/usr/local/sbin/bird -p  
ExecReload=/usr/local/sbin/birdc configure  
ExecStart=/usr/local/sbin/bird -f -u bird -g bird  
Restart=on-abort  
  
[Install]  
WantedBy=multi-user.target
```

```
systemctl enable --now bird
```

bird2 konfigurieren

</usr/local/etc/bird.conf>

From:

<https://wiki.clerie.de/> - **clerie's Wiki**

Permanent link:

<https://wiki.clerie.de/notiz/bird2-debian-buster-installieren?rev=1605647806>

Last update: **2020/11/17 22:16**

