

bird 2 auf Debian Buster installieren

Abhängigkeiten installieren

```
apt install build-essential autotools-dev autoconf flex bison libncurses-dev libreadline-dev
```

bird2 bauen und installieren

```
wget https://bird.network.cz/download/bird-2.0.7.tar.gz
tar -xf bird-2.0.7.tar.gz
ls -al
cd bird-2.0.7/
./configure
make -j 2
sudo make install
```

bird2 einrichten

```
adduser --system --group --no-create-home bird
```

</etc/systemd/system/bird.service>

```
[Unit]
Description=BIRD Internet Routing Daemon
After=network.target

[Service]
ExecStartPre=/usr/local/sbin/bird -p
ExecReload=/usr/local/sbin/birdc configure
ExecStart=/usr/local/sbin/bird -f -u bird -g bird
Restart=on-abort

[Install]
WantedBy=multi-user.target
```

```
systemctl enable --now bird
```

bird2 konfigurieren

[/usr/local/etc/bird.conf](#)

```
router id 192.168.10.26;
ipv6 table ospf6;
ipv6 table bgp6;
protocol direct {
    interface "ens20";
    ipv6 {
        table ospf6;
    };
}
protocol static {
    ipv6 {
        table bgp6;
    };
    route fd56:4902:eca0::/48 via "lo";
    route fd56:4902:eca0::/52 via "lo";
}
protocol kernel {
    ipv6 {
        table ospf6;
        export filter {
            krt_prefsrc=fd56:4902:eca0:6::1;
            accept;
        };
        import none;
    };
    kernel table 1337;
}
protocol kernel {
    ipv6 {
        table bgp6;
        export filter {
            krt_prefsrc=fd56:4902:eca0:6::1;
            accept;
        };
        import none;
    };
    kernel table 2342;
}

protocol ospf v3 {
    ipv6 {
        table ospf6;
        import all;
        export all;
    };
    area 0 {
        interface "ens19" {
            cost 80;
        };
    };
}
```

```
};
}

protocol bgp gw5 {
    local as 4242422574;
    graceful restart on;
    neighbor fd56:4902:eca0:5::1 as 4242422574;
    source address fd56:4902:eca0:6::1;
    ipv6 {
        table bgp6;
        igp table ospf6;
        next hop self;
        import keep filtered;
        import all;
        export all;
    };
}

protocol bgp peer_nex {
    local as 4242422574;
    graceful restart on;
    neighbor fd9b:37f7:faf7:3001::2 as 4242423012;
    source address fd9b:37f7:faf7:3001::6;
    ipv6 {
        table bgp6;
        igp table ospf6;
        next hop self;
        import keep filtered;
        import filter {
            if net ~ [fd00::/8{8,64}] then accept;
            reject;
        };
        export filter {
            #if net ~ [fd9b:37f7:faf7:3001::/64] then
reject;
            if net ~ [fd00::/8{8,64}] then accept;
            reject;
        };
    };
}

protocol device {
    scan time 10;
}
```

From:

<https://wiki.clerie.de/> - **clerie's Wiki**

Permanent link:

<https://wiki.clerie.de/notiz/bird2-debian-buster-installieren?rev=1605647899>

Last update: **2020/11/17 22:18**

