

# clerie's Gentoo install Guide

## Konzept

- Vollverschlüsselte Festplatte
- (U)EFI Boot direkt in den Kernel
- Hibernate

## Links

- [https://wiki.gentoo.org/wiki/Full\\_Disk\\_Encryption\\_From\\_Scratch\\_Simplified](https://wiki.gentoo.org/wiki/Full_Disk_Encryption_From_Scratch_Simplified)

## Partitionierung

/boot/efi		512MB	mkfs.fat -F 32
/boot		1G	mkfs.ext4
lvm	/	25GB	
	swap	RAM+2GB	
	/home	100%FREE	

## Krypto

```
cryptsetup luksFormat -c aes-xts-plain64 -hash sha256 -s 256 /dev/nvme0n1p3
```

## LVM

```
cryptsetup luksOpen /dev/nvme0n1p3 lvm
```

```
pvccreate /dev/mapper/lvm
```

```
vgcreate vg0 /dev/mapper/lvm
```

```
lvcreate -L50G -n root vg0
```

```
lvcreate -L18G -n swap vg0
```

```
lvcreate -l 100%FREE -n home vg0
```

```
mkfs.ext4 /dev/mapper/vg0-root
```

```
mkswap /dev/mapper/vg0-swap swapon /dev/mapper/vg0-swap
```

```
mkfs.ext4 /dev/mapper/vg0-home
```

## Partitionen einhängen

```
mkdir /mnt/gentoo
```

```
mount /dev/mapper/vg0-root /mnt/gentoo
```

```
mkdir /mnt/gentoo/home
```

```
mount /dev/mapper/vg0-home /mnt/gentoo/home
```

```
mkdir /mnt/gentoo/boot
```

```
mount /dev/nvme0n1p2 /mnt/gentoo/boot
```

```
mkdir /mnt/gentoo/boot/efi
```

```
mount /mnt/nvme0n1p1 /mnt/gentoo/boot/efi
```

```
cd /etc/gentoo
```

## Gentoo laden

```
wget
```

```
https://linux.rz.ruhr-uni-bochum.de/download/gentoo-mirror/releases/amd64/autobuilds/current-stage3-amd64/stage3-amd64-20200722T214503Z.tar.xz
```

```
https://linux.rz.ruhr-uni-bochum.de/download/gentoo-mirror/
```

```
tar xvf stage3-amd64-20200722T214503Z.tar.xz -xattrs -numeric-owner
```

## Repos konfigurieren

```
mkdir etc/portage/repos.conf
```

```
cp usr/share/portage/config/repos.conf etc/portage/repos.conf/gentoo.conf
```

## chroot vorbereiten

```
cp /etc/resolv.conf etc/resolv.conf
```

```
mount -t proc /proc proc mount -rbind /sys sys mount -make-rslave sys mount -rbin /dev dev mount -make-rslave dev
```

## chrooten

```
chroot /mnt/gentoo /bin/bash
```

```
source /etc/profile
```

```
export PS1=„(chroot) $PS1“
```

## Portage konfigurieren

[/etc/portage/make.conf](#)

```
# These settings were set by the catalyst build script that
# automatically
# built this stage.
# Please consult /usr/share/portage/config/make.conf.example for a more
# detailed example.
COMMON_FLAGS="-march=native -O2 -pipe"
CFLAGS="${COMMON_FLAGS}"
CXXFLAGS="${COMMON_FLAGS}"
FCFLAGS="${COMMON_FLAGS}"
FFLAGS="${COMMON_FLAGS}"

# NOTE: This stage was built with the bindist Use flag enabled
PORTDIR="/var/db/repos/gentoo"
DISTDIR="/var/cache/distfiles"
PKGDIR="/var/cache/binpkgs"

# This sets the language of build output to English.
# Please keep this setting intact when reporting bugs.
LC_MESSAGES=C

MAKEOPTS="-j5"

GENTOO_MIRRORS="ftp://ftp.wh2.tu-dresden.de/pub/mirrors/gentoo
https://linux.rz.ruhr-uni-bochum.de/do
wnload/gentoo-mirror/
http://linux.rz.ruhr-uni-bochum.de/download/gentoo-mirror/
https://ftp.halifax.
rwth-aachen.de/gentoo/ http://ftp.halifax.rwth-aachen.de/gentoo/
ftp://ftp.halifax.rwth-aachen.de/gen
too/ rsync://ftp.halifax.rwth-aachen.de/gentoo/
https://ftp.fau.de/gentoo http://ftp.fau.de/gentoo ft
p://ftp.fau.de/gentoo rsync://ftp.fau.de/gentoo
https://ftp-stud.hs-esslingen.de/pub/Mirrors/gentoo/
http://ftp-stud.hs-esslingen.de/pub/Mirrors/gentoo/
ftp://ftp-stud.hs-esslingen.de/pub/Mirrors/gentoo
/ rsync://ftp-stud.hs-esslingen.de/gentoo/"
```

```
USE=""  
  
EMERGE_DEFAULT_OPTS="--ask --tree --quiet --verbose"  
  
VIDEO_CARDS="intel"  
INPUT_DEVICES="libinput"
```

## Portage Dateien laden

emerge-webrsync

## Profil wählen

eselect profile set „default/linux/amd64/17.1/desktop/gnome“

## Locales setzen

echo „Europe/Berlin“ > /etc/timezone

emerge -config sys-libs/timezone-data

[/etc/locale.gen](#)

```
en_GB ISO-8859-1  
en_GB.UTF-8 UTF-8  
de_DE ISO-8859-1  
de_DE.UTF-8 UTF-8
```

locale-gen

eselect locale list

eselect locale set X

env-update && source /etc/profile

PS1=„(chroot) \$PS1“

## fstab konfigurieren

blkid

[/etc/fstab](#)

```
UUID="FDE1-7057" /boot/efi vfat noauto,noatime 0 2
UUID="e8fb3fec-568b-45f5-879d-d19c34064940" /boot ext4 defaults 0 2
UUID="ea605252-8052-479a-a138-db0a5183de0c" / ext4 defaults 0 1
UUID="a994233d-d063-4340-a174-a0600e62151d" /home ext4 defaults 0 1
UUID="28e5ee39-6d32-46ea-82b7-b84768ad8d47" none swap sw 0 0
```

## Genkernel und Grub

### Kernel Sources laden

emerge sys-kernel/gentoo-sources emerge sys-kernel/genkernel emerge sys-fs/cryptsetup

## DIY Kernel

### Kernel Konfig

- Wir wollen direkt vom Kernel booten
  - [https://wiki.gentoo.org/wiki/EFI\\_System\\_Partition](https://wiki.gentoo.org/wiki/EFI_System_Partition)
  - [https://wiki.gentoo.org/wiki/EFI\\_stub\\_kernel](https://wiki.gentoo.org/wiki/EFI_stub_kernel)

From:

<https://wiki.clerie.de/> - **clerie's Wiki**

Permanent link:

<https://wiki.clerie.de/notiz/gentoo-installieren?rev=1595497851>

Last update: **2020/07/23 11:50**

