Postfix Mailrelay

/etc/postfix/main.cf

```
# See /usr/share/postfix/main.cf.dist for a commented, more complete
version


# Debian specific:  Specifying a file name will cause the first
# line of that file to be used as the name.  The Debian default
# is /etc/mailname.
#myorigin = /etc/mailname

smtpd_banner = $myhostname ESMTP $mail_name (Debian/GNU)
biff = no

# appending .domain is the MUA's job.
append_dot_mydomain = no

# Uncomment the next line to generate "delayed mail" warnings
#delay_warning_time = 4h

readme_directory = no

# See http://www.postfix.org/COMPATIBILITY_README.html -- default to 2
on
# fresh installs.
compatibility_level = 2

# TLS parameters
smtpd_tls_cert_file=/etc/ssl/certs/ssl-cert-snakeoil.pem
smtpd_tls_key_file=/etc/ssl/private/ssl-cert-snakeoil.key
smtpd_use_tls=yes
smtpd_tls_session_cache_database = btree:${data_directory}/smtpd_scache
smtp_tls_session_cache_database = btree:${data_directory}/smtp_scache
smtp_tls_wrappermode = yes
smtp_tls_security_level = encrypt
smtp_sasl_auth_enable = yes
smtp_sasl_security_options =
smtp_sasl_password_maps = hash:/etc/postfix/sasl_password

smtpd_relay_restrictions = permit_mynetworks permit_sasl_authenticated
defer_unauth_destination
myhostname = web-1.net.clerie.de
alias_maps = hash:/etc/aliases
alias_database = hash:/etc/aliases
myorigin = /etc/mailname
mydestination = $myhostname, web-1.net.clerie.de,
localhost.net.clerie.de, localhost
```

```
relayhost = [mail-1.net.clerie.de]:465
mynetworks = 127.0.0.0/8 [::ffff:127.0.0.0]/104 [::1]/128
mailbox_size_limit = 0
recipient_delimiter = +
inet_interfaces = loopback-only
inet_protocols = all
```

/etc/postfix/sasl_password

```
[mail-1.net.clerie.de]:465 auth-only@net.clerie.de:password
```

```
postmap /etc/postfix/sasl_password
```

/etc/aliases

```

```

```
newaliases
```

From:
https://wiki.clerie.de/ - **clerie's Wiki**

Permanent link:
https://wiki.clerie.de/notiz/postfix-mailrelay?rev=1598288036

Last update: **2020/08/24 18:53**